

Katalog

Halbleiterrelais

von **ZETTLER** electronics
A ZETTLER GROUP COMPANY



MOSFET Relay Selector Tool



Coto Part Number	Contact Form	Package Style	Load Voltage (V)	Load Current (mA)	Ron Typ. -	Cout Typ. (pF)	Turn On Time Typ. (mS)	Turn Off Time Typ. (mS)
C208S	1A	SOP-4 Pin	100	150	6.00	50	0.30	0.10
C217S	1A	SOP-4 Pin	60	130	7.00	50	0.30	0.10
CS230-HC	1A	SMD-4 Pin	350	130	22.00	41	0.30	0.05
C212S	1A	SOP-4 Pin	60	400	0.83	50	0.30	0.10
CT136-HT	1A	DIP-6 Pin	60	500	0.12	470	2.20	0.40
CS136-HT	1A	SMD-6 Pin	60	500	0.12	470	2.20	0.40
C236S-HT	1A	SOP-4 Pin	60	350	0.13	115	1.00	0.60
C226S	1A	SOP-4 Pin	40	2,000	0.09	240	0.50	0.04
C326S	2A	SOP-8 Pin	40	1,600	0.09	240	0.50	0.04
CT226	1A	DIP-4 Pin	40	2,000	0.09	240	0.50	0.05
CS226	1A	SMD-4 Pin	40	2,000	0.09	240	0.50	0.05
CT126	1A	DIP-6 Pin	40	2,000	0.09	240	0.50	0.05

Coto Part Number	Contact Form	Package Style	Load Voltage (V)	Load Current (mA)	Ron Typ. -	Cout Typ. (pF)	Turn On Time Typ. (mS)	Turn Off Time Typ. (mS)
CS126	1A	SMD-6 Pin	40	2,000	0.09	240	0.50	0.05
CT326	2A	DIP-8 Pin	40	2,000	0.09	240	0.50	0.05
CS326	2A	SMD-8 Pin	40	2,000	0.09	240	0.50	0.05
C230S	1A	SOP-4 Pin	400	100	24.00	115	0.25	0.02
C330S	2A	SOP-8 Pin	400	85	24.00	115	0.25	0.02
CT230	1A	DIP-4 Pin	400	120	24.00	115	0.20	0.05
CS230	1A	SMD-4 Pin	400	120	24.00	115	0.20	0.05
CT130	1A	DIP-6 Pin	400	120	24.00	115	0.20	0.05
CS130	1A	SMD-6 Pin	400	120	24.00	115	0.20	0.05
CT330	2A	DIP-8 Pin	400	100	24.00	115	0.20	0.05
CS330	2A	SMD-8 Pin	400	100	24.00	115	0.20	0.05
C231S	1A	SOP-4 Pin	350	120	17.00	115	0.25	0.05
C331S	2A	SOP-8 Pin	350	100	17.00	115	0.25	0.05
CT231	1A	DIP-4 Pin	350	130	17.00	115	0.20	0.05
CS231	1A	SMD-4 Pin	350	130	17.00	115	0.20	0.05
CT131	1A	DIP-6 Pin	350	130	17.00	115	0.20	0.05
CS131	1A	SMD-6 Pin	350	130	17.00	115	0.20	0.05
CT331	2A	DIP-8 Pin	350	110	17.00	115	0.20	0.05
CS331	2A	SMD-8 Pin	350	110	17.00	115	0.20	0.05
C234S	1A	SOP-4 Pin	200	180	6.00	130	0.25	0.05
C334S	2A	SOP-8 Pin	200	160	6.00	130	0.25	0.05

Coto Part Number	Contact Form	Package Style	Load Voltage (V)	Load Current (mA)	Ron Typ. -	Cout Typ. (pF)	Turn On Time Typ. (mS)	Turn Off Time Typ. (mS)
CT234	1A	DIP-4 Pin	200	200	6.00	130	0.20	0.05
CS234	1A	SMD-4 Pin	200	200	6.00	130	0.20	0.05
CT134	1A	DIP-6 Pin	200	200	6.00	130	0.20	0.05
CS134	1A	SMD-6 Pin	200	200	6.00	130	0.20	0.05
CT334	2A	DIP-8 Pin	200	180	6.00	130	0.20	0.05
CS334	2A	SMD-8 Pin	200	180	6.00	130	0.20	0.05
C235S	1A	SOP-4 Pin	80	80	20.00	6	0.02	0.05
C335S	2A	SOP-8 Pin	80	70	20.00	6	0.02	0.05
CT235	1A	DIP-4 Pin	80	100	20.00	6	0.02	0.05
CS235	1A	SMD-4 Pin	80	100	20.00	6	0.02	0.05
CT135	1A	DIP-6 Pin	80	100	20.00	6	0.02	0.05
CS135	1A	SMD-6 Pin	80	100	20.00	6	0.02	0.05
CT335	2A	DIP-8 Pin	80	80	20.00	6	0.02	0.05
CS335	2A	SMD-8 Pin	80	80	20.00	6	0.02	0.05
CT136	1A	DIP-6 Pin	60	2,500	0.09	470	0.60	0.04
CS136	1A	SMD-6 Pin	60	2,500	0.09	470	0.60	0.04
C237S	1A	SOP-4 Pin	60	350	0.80	195	0.35	0.05

Firosu GmbH

Jahnstrasse 32a
92237 Sulzbach-Rosenberg
Deutschland

tel: +49 9661 906236 | fax: +49 9661 102451
mail: info@firosu.de | web: www.firosu.de